

Page: 1 / 9
Revised edition no: 2 - 02

Date: 2/3/2015

Supersedes: 28 / 8 / 2012

097A_06

ALPHAGAZ™ 2 OXYGEN

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : ALPHAGAZ™ 2 OXYGEN

SDS Nr : 097A_06 Chemical description : Oxygen

CAS No :7782-44-7 EC No :231-956-9 Index No :008-001-00-8

Registration-No. : Listed in Annex IV / V REACH, exempted from registration.

Chemical formula : O2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.

Test gas / Calibration gas.

Laboratory use.

Use for manufacture of electronic/photovoltaic components.

Laser gas.

Contact supplier for more uses information.

1.3. Details of the supplier of the safety data sheet

Company identification : AIR LIQUIDE Deutschland GmbH

Hans-Günther-Sohl-Straße 5 D-40235 Düsseldorf GERMANY

Telefon: +49 (0)211 6699-0 - Fax: +49 (0)211 6699-222

E-Mail address (competent person) : Info.SDB@AirLiquide.de

1.4. Emergency telephone number

Emergency telephone number : +49 (0)2151 398668

- Availability : (24 / 7)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

• Physical hazards : Oxidizing gases - Category 1 - Danger - (CLP : Ox. Gas 1) - H270

Gases under pressure - Compressed gas - Warning - (CLP : Press. Gas) - H280

In case of emergency: +49 (0)2151 398668

Classification EC 67/548 or EC 1999/45

Classification : O; R8

2.2. Label elements

Labelling Regulation EC 1272/2008 (CLP)

Hazard pictograms





• Hazard pictograms code : GHS03 - GHS04

• Signal words : Danger

• Hazard statements : H270 - May cause or intensify fire; oxidizer.

H280 - Contains gas under pressure; may explode if heated.

• Precautionary statements



Page: 2 / 9

Revised edition no: 2 - 02

Date: 2 / 3 / 2015

Supersedes : 28 / 8 / 2012

097A 06

ALPHAGAZ™ 2 OXYGEN

SECTION 2. Hazards identification (continued)

- Prevention : P244 - Keep valves and fittings free from oil and grease

P220 - Keep away from combustible materials.

- Response : P370+P376 - In case of fire : Stop leak if safe to do so.

- Storage : P403 - Store in a well-ventilated place.

2.3. Other hazards

Other hazards : None.

SECTION 3. Composition/information on ingredients

3.1. Substance / 3.2. Mixture

Substance.

Substance name		Content [Vol-%]	CAS No EC No Index No Registration no.	Classification(DSD)	Classification(CLP)
Oxygen	:	100 %	7782-44-7 231-956-9 008-001-00-8	O; R8	Ox. Gas 1 (H270) Press. Gas (H280)
			+ 4		

Contains no other components or impurities which will influence the classification of the product.

- * 1: Listed in Annex IV / V REACH, exempted from registration.
- * 2: Registration deadline not expired.
- * 3: Registration not required: Substance manufactured or imported < 1t/y
 Full text of R-phrases see chapter 16. Full text of H-statements see chapter 16

SECTION 4. First aid measures

4.1. Description of first aid measures

Inhalation
 Skin contact
 Adverse effects not expected from this product.
 Eye contact
 Adverse effects not expected from this product.

4.2. Most important symptoms and effects, both acute and delayed

: Continuous inhalation of concentrations higher than 75% may cause nausea, dizziness,

In case of emergency: +49 (0)2151 398668

respiratory difficulty and convulsion.

4.3. Indication of any immediate medical attention and special treatment needed

: None.



Page: 3 / 9

Revised edition no: 2 - 02

Date: 2 / 3 / 2015

Supersedes : 28 / 8 / 2012

097A_06

ALPHAGAZ™ 2 OXYGEN

SECTION 5. Fire-fighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.

- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Exposure to fire may cause containers to rupture/explode.

Supports combustion.

Hazardous combustion products : None.

5.3. Advice for firefighters

Specific methods : Move containers away from the fire area if this can be done without risk.

If possible, stop flow of product.

Use fire control measures appropriate to the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering

sewers and drainage systems.

Use water spray or fog to knock down fire fumes if possible.

Special protective equipment for fire

fighters

None necessary.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

face mask.

Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire

fighters.

Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for

firefighters

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

: Ensure adequate air ventilation.

Eliminate ignition sources

Evacuate area

Prevent from entering sewers, basements and workpits, or any place where its accumulation

In case of emergency: +49 (0)2151 398668

can be dangerous.

Try to stop release.

Monitor concentration of released product.

6.2. Environmental precautions

: Try to stop release.

6.3. Methods and material for containment and cleaning up

: Ventilate area.

6.4. Reference to other sections

Reference to other sections : See also sections 8 and 13.



Page: 4/9 Revised edition no: 2 - 02 Date: 2/3/2015

Supersedes: 28 / 8 / 2012

097A 06

ALPHAGAZ™ 2 OXYGEN

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Safe use of the product

: Do not breathe gas.

Avoid release of product into atmosphere.

Use no oil or grease.

Use only properly specified equipment which is suitable for this product, its supply pressure

and temperature. Contact your gas supplier if in doubt.

Do not smoke while handling product. Keep equipment free from oil and grease.

Use only oxygen approved lubricants and oxygen approved sealings.

Only experienced and properly instructed persons should handle gases under pressure. Ensure the complete gas system was (or is regularily) checked for leaks before use. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. The product must be handled in accordance with good industrial hygiene and safety

procedures.

Consider pressure relief device(s) in gas installations.

Safe handling of the gas receptacle

Suck back of water into the container must be prevented.

Open valve slowly to avoid pressure shock

Refer to supplier's container handling instructions.

Do not allow backfeed into the container.

Replace valve outlet caps or plugs and container caps where supplied as soon as container is

disconnected from equipment.

Protect cylinders from physical damage; do not drag, roll, slide or drop.

Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.)

designed to transport cylinders.

Leave valve protection caps in place until the container has been secured against either a wall

or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating cylinder valve discontinue use and contact

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to repair or modify container valves or safety relief devices.

Keep container valve outlets clean and free from contaminants particularly oil and water.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container.

Damaged valves should be reported immediately to the supplier.

7.2. Conditions for safe storage, including any incompatibilities

Keep container below 50°C in a well ventilated place.

Segregate from flammable gases and other flammable materials in store. Store containers in location free from fire risk and away from sources of heat and ignition. Stored containers

should be periodically checked for general condition and leakage.

Containers should not be stored in conditions likely to encourage corrosion. Containers should be stored in the vertical position and properly secured to prevent toppling. Container valve

In case of emergency: +49 (0)2151 398668

guards or caps should be in place. Keep away from combustible materials.

7.3. Specific end use(s)

· None



Page: 5/9 Revised edition no : 2 - 02 Date: 2/3/2015

Supersedes: 28 / 8 / 2012

097A_06

In case of emergency: +49 (0)2151 398668

ALPHAGAZ™ 2 OXYGEN

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

DNEL: Derived no effect level (

Workers)

No data available

PNEC: Predicted no effect

concentration

: No data available.

8.2. Exposure controls

8.2.1. Appropriate engineering

controls

: Avoid oxygen rich (>21%) atmospheres.

Provide adequate general and local exhaust ventilation.

Systems under pressure shoud be regularily checked for leakages. Gas detectors should be used when oxidising gases may be released.

Consider work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, :

e.g. personal protective equipment

Wear suitable hand, body and head protection. Wear goggles with suitable filter lenses when

use is cutting/welding.

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.

The following recommendations should be considered.

PPE compliant to the recommended EN/ISO standards should be selected.

· Eye/face protection

Wear safety glasses with side shields Standard EN 166 - Personal eye-protection.

Skin protection

: Wear working gloves when handling gas containers. - Hand protection

Standard EN 388 - Protective gloves against mechanical risk.

- Other

Consider the use of flame resistant safety clothing. Standard EN ISO 14116 - Limited flame spread materials.

Wear safety shoes while handling containers.

Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

 Thermal hazards 8.2.3. Environmental exposure

controls

: None necessary : None necessary.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state at 20°C / 101.3kPa : Gas. Colour : Colourless.

Odour : No odour warning properties.

Odour threshold : Odour threshold is subjective and inadequate to warn for overexposure.

pH value : Not applicable.

Molar mass [g/mol] : 32 Melting point [°C] : -219 Boiling point [°C] -183 : -118 Critical temperature [°C]

Flash point [°C] : Not applicable for gases and gas-mixtures. Evaporation rate (ether=1) : Not applicable for gases and gas-mixtures.

Flammability range [vol% in air] : Non flammable.



Page: 6/9 Revised edition no : 2 - 02 Date: 2/3/2015

Supersedes: 28 / 8 / 2012

097A 06

ALPHAGAZ™ 2 OXYGEN

SECTION 9. Physical and chemical properties (continued)

: Not applicable. Vapour pressure [20°C]

Relative density, gas (air=1) · 11 Relative density, liquid (water=1) · 11 Solubility in water [mg/l] : 39

Partition coefficient n-octanol/water [: Not applicable for inorganic gases.

log Pow]

: Not applicable. Auto-ignition temperature [°C] Viscosity at 20°C [mPa.s] : Not applicable. **Explosive Properties** : Not applicable. **Oxidising properties** : Oxidiser. None.

- Coefficient of oxygen equivalency (

Ci) ISO10156: 9.2. Other information

Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below

ground level.

SECTION 10. Stability and reactivity

10.1. Reactivity

: No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

: Stable under normal conditions.

10.3. Possibility of hazardous reactions

: Violently oxidises organic material.

10.4. Conditions to avoid

: None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

: May react violently with combustible materials. May react violently with reducing agents.

Consider the potential toxicity hazard due to the presence of chlorinated or fluorinated

In case of emergency: +49 (0)2151 398668

polymers in high pressure (> 30 bars) oxygen lines in case of combustion

Keep equipment free from oil and grease.

For additional information on compatibility refer to ISO 11114

10.6. Hazardous decomposition products

: None.



Page: 7 / 9

Revised edition no: 2 - 02

Date: 2 / 3 / 2015

Supersedes : 28 / 8 / 2012

097A 06

ALPHAGAZ™ 2 OXYGEN

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity : No known toxicological effects from this product.

Skin corrosion/irritation : No known effects from this product. Serious eye damage/irritation : No known effects from this product. Respiratory or skin sensitisation : No known effects from this product. Carcinogenicity : No known effects from this product. Germ cell mutagenicity : No known effects from this product. Reproductive toxicity : No known effects from this product. : No known effects from this product. STOT-single exposure STOT-repeated exposure : No known effects from this product. Aspiration hazard : Not applicable for gases and gas-mixtures.

SECTION 12. Ecological information

12.1. Toxicity

Assessment : No ecological damage caused by this product.

12.2. Persistence and degradability

Assessment : No ecological damage caused by this product.

12.3. Bioaccumulative potential

Assessment : No ecological damage caused by this product.

12.4. Mobility in soil

Assessment : No ecological damage caused by this product.

12.5. Results of PBT and vPvB assessment

: Not classified as PBT or vPvB.

12.6. Other adverse effects

Effect on ozone layer : None.
Effect on the global warming : None.

SECTION 13. Disposal considerations

13.1. Waste treatment methods

: May be vented to atmosphere in a well ventilated place.

Do not discharge into any place where its accumulation could be dangerous.

Refer to the code of practice of EIGA (Doc. 30/10 "Disposal of Gases, downloadable at http://

www.eiga.org) for more guidance on suitable disposal methods

List of hazardous waste codes (from Commission Decision 2001/118/EC)

: 16 05 04: Gases in pressure containers (including halons) containing dangerous substances.

In case of emergency: +49 (0)2151 398668

13.2. Additional information

: None.



Page: 8/9

Revised edition no: 2 - 02

Date: 2/3/2015

Supersedes: 28 / 8 / 2012

097A 06

ALPHAGAZ™ 2 OXYGEN

SECTION 14. Transport information

14.1. UN number

UN number : 1072

Labelling ADR, IMDG, IATA





: 2.2 : Non flammable, non toxic gas. 5.1: Oxidizing substances.

14.2. UN proper shipping name

Transport by road/rail (ADR/RID)

OXYGEN, COMPRESSED

Transport by air (ICAO-TI / IATA-DGR) : OXYGEN, COMPRESSED Transport by sea (IMDG) : OXYGEN, COMPRESSED

14.3. Transport hazard class(es)

Transport by road/rail (ADR/RID)

Class : 2 Classification code : 10 HI nr : 25

Tunnel Restriction : E : Passage forbidden through tunnels of category E.

Transport by air (ICAO-TI / IATA-DGR)

Transport by sea (IMDG)

Emergency Schedule (EmS) - Fire : F-C Emergency Schedule (EmS) - Spillage : S-W

14.4. Packing group

Transport by road/rail (ADR/RID) : Not applicable. Transport by air (ICAO-TI / IATA-DGR) : Not applicable. Transport by sea (IMDG) : Not applicable.

14.5. Environmental hazards

Transport by road/rail (ADR/RID) · None Transport by air (ICAO-TI / IATA-DGR) : None. Transport by sea (IMDG)

14.6 Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P200

Transport by air (ICAO-TI / IATA-DGR)

: Allowed. Passenger and Cargo Aircraft Packing instruction - Passenger and : 200 Cargo Aircraft

Cargo Aircraft only

Packing instruction - Cargo Aircraft

Transport by sea (IMDG) : P200

: - Ensure there is adequate ventilation. Special precautions for user

: Allowed.

: 200

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the

In case of emergency: +49 (0)2151 398668

event of an accident or an emergency. Before transporting product containers:

- Ensure that containers are firmly secured.



Page: 9/9 Revised edition no: 2 - 02 Date: 2/3/2015

Supersedes: 28 / 8 / 2012

097A 06

ALPHAGAZ™ 2 OXYGEN

SECTION 14. Transport information (continued)

- Ensure cylinder valve is closed and not leaking.

- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.

- Ensure valve protection device (where provided) is correctly fitted.

Avoid transport on vehicles where the load space is not separated from the driver's compartment

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Transport in bulk according to Annex : Not applicable. II of MARPOL 73/78 and the IBC Code

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Restrictions on use : None. Seveso directive 96/82/EC : Listed.

National legislation

: Ensure all national/local regulations are observed.

- 4. BlmschV (Germany)

- Water hazard class (WGK) : WGK Germany: Not hazardous to waters.

- Other regulations and technical rules : [German regulations]

(not complete)

BetriebssicherheitsV mit TRBSen insbesondere TRBS 3145 / TRGS 725 "Ortsbewegliche Druckgasbehälter", TRGS 2141, BGRegel 500 Teil 2.33: "Umgang mit Gasen", GefahrstoffV mit Technischen Regeln Gefährliche Stoffe TRGS insbesondere TRGS 407 "Tätigkeiten mit

Gasen - Gefährdungsbeurteilung", TRGS 400, 500, 510, 900.

15.2. Chemical safety assessment

: A CSA does not need to be carried out for this product.

SECTION 16. Other information

: Revised safety data sheet in accordance with commisssion regulation (EU) No 453/2010 Indication of changes

Training advice : Ensure operators understand the hazard of oxygen enrichment.

Further information This Safety Data Sheet has been established in accordance with the applicable European

Union legislation.

List of full text of R-phrases in section: R8: Contact with combustible material may cause fire.

List of full text of H-statements in : H270 - May cause or intensify fire; oxidizer.

section 3. H280 - Contains gas under pressure; may explode if heated.

DISCLAIMER OF LIABILITY : Before using this product in any new process or experiment, a thorough material compatibility

and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or

damage resulting from its use can be accepted.

End of document

In case of emergency: +49 (0)2151 398668